



NOTES:

1. ALL LATERAL STREET CUTS MUST BE COVERED WITH A STEEL PLATE OF SUFFICIENT THICKNESS TO SPAN THE CUT WITHOUT NOTICEABLE DEFLECTION. PLATES TO REMAIN IN PLACE UNTIL THE CONCRETE BASE HAS GAINED SUFFICIENT STRENGTH TO WITH STAND TRAFFIC LOADS (24 HR MIN.). WITHIN NOT LONGER THAN SEVEN CALENDAR DAYS OF BEGINNING OF CONCRETE POUR THE AREA WILL BE TOPPED OUT.
2. WHERE COMPACTION CAN NOT BE OBTAINED WITH EARTH MATERIALS,USE NO.57 OR FLOW ABLE FILL AS DETERMINED BY ACC INSPECTOR.
3. WORK TO BE INSPECTED BY THE ATHENS CLARKE COUNTY TRANSPORTATION AND PUBLIC WORKS INSPECTOR.

Paving Cut Detail  
NTS

G-1

Standard Specification and Detail for:

*Paving Cut Detail*

|         |                       |                |                    |
|---------|-----------------------|----------------|--------------------|
| GMD: NA | County: Athens-Clarke | State: Georgia | Date: August, 2019 |
|---------|-----------------------|----------------|--------------------|

|                 |
|-----------------|
| Drawn by: KFM   |
| Approved by: GJ |
| Scale: AS-SHOWN |

The Unified Government of Athens-Clarke County  
**Department of Public Utilities**  
 124 E Hancock Ave  
 Athens, Georgia 30601  
 Fax: 706-613-3198      Voice: 706-613-3490

